

RGB-10mm series

COB | 15W/m | 10mm

COB

p/n: VFL-MCCOB-RGB-840-10-24V15



Features

- High output RGB
- 24V input
- **Hotspot-free appearance**
- RGB controlled by PWM controller
- Durable, flexible and low profile
- Double sided 3M tape mounting

Electrical Data

Voltage	24V DC
Wattage per meter	15W
Current per meter	0.625A/24V

LED Data

LED type	COB
Manufacturer	SAN'AN
Chips per meter	840

Photometric Data

Color temperature	RGB
Color rendering index Ra	-
Luminous flux per meter	R: 128 lm G: 389 lm B: 59 lm RGB: 526 lm
Luminous efficacy	35 lm/W RGB
Beam angle	135°
Dimmable	0~100%

Construction / Protection

Substrate	Double layer FPCB
Thickness of FPCB	2 oz
Mounting	Double sided tape 3M
IP rating	See figure 3.
Operating temperature	-20 ~ +45 C°
Storage temperature	-20 ~ +70 C°

Dimensions

Cutting increments	50 mm
	See figure 1.
Length	5,000 mm
Width	10 mm
Height	1.6 mm

Lifetime

Lifespan (L70)	>54,000 hours
----------------	---------------

Testing environment temperature = 25 C°




Figure 1.

Dimensions & Cutting increments





Figure 2.

Suitable Accessories

Connector



Profile



Figure 3.

IP Protection Ratings

