Basic series

SMD 2835 | 10mm (0.39in)

SMD

p/n: VFL-BS2835-930K-140-10-24V14

Features

- 140x SMD LED per meter (42xSMD LEDs per foot)
- Cost effective
- Up to 1,700Lm/m (518Lm/ft)
- High efficacy of 118Lm/W
- CRI>90
- Durable, flexible and low profile
- Double sided 3M tape mounting

Electrical Data

Voltage	24V DC
Wattage	**14.4W/m** (4.39W/ft)
Current	0.6A/m (0.18A/ft)/24V

LED Data

LED type	**SMD 2835**
Manufacturer	Lumileds
Chips	140 Led/m (42 Led/ft)

Photometric Data

Color temperature	2700K / 3000K / 3500K 4000K / 6500K
Color redering index Ra	>90
Luminous flux	1,789 Lm/m (545 Lm/ft) @ 4000K 1,700 Lm/m (518 Lm/ft) @ 3000K
Luminous efficacy	118 Lm/W @ 3000K
Beam angle	120°
Dimmable	0~100%

Construction / Protection

Substrate	Double layer FPCB
Thickness of FPCB	2 oz
Mounting	Double sided tape 3M
IP rating	See figure 3.
Operating temperature	-20 ~ +50 °C (-4 ~ 122 °F)
Storage temperature	-20 ~ +70 °C (-4 ~ 158 °F)

Dimensions

Cutting increments	50 mm (1.97 in) See figure 1.
Length	5 m (16.4 ft)
Width	10 mm (0.39 in)
Height	1.6 mm (0.06 in)

Lifetime

Lifespan (L70)	>54,000 hours

Testing environment temperature = 25 °C (77°F)

Figure 1.

Dimensions & Cutting increments



Figure 2.

Suitable Accessories

Connector-IP20/IP54

Code: MX-FC-2P-10
Feeding connector with 2-wire cable 150mm (5.91in)

Code: MX-JC-2P-10
Joint connector with 2-wire cable 150mm (5.91in)

Code: MX-TC-2P-10
T-shaped connector

Code: MX-MC-2P-10
Middle connector

Profile

Surface-Mount
Code: VL-SF1507

Recessed-Mount
Code: VL-RC2207

Corner-Mount
Code: VL-TR1616

Figure 3.

IP Protection Ratings



- LED
- FPCB
- Silicone Gel
- Double-sided tape 3M 300LSE (indoor)
- Double-sided tape 3M VHB (outdoor)

Figure 4.

Ordering Code

	Series	LED type		CRI	CCT		LED Qty		PCB Width		IP Rating		Voltage	Power/m
VFL	- BS	2835	-	9	xxK	-	140	-	10	-	WPyy	-	24V	14
				9 - 90+ 8 - 80+	27K - 2700K 30K - 3000K 35K - 3500K 40K - 4000K 65K - 6500K						Blank - IP20 54 - IP54 65 - IP65 67 - IP67 68 - IP68			