



VL-SI1212-W (Small Wave series - top bend)



FEATURES

Fully automated extrusion silicone LED flexible neon, offering smooth, linear decorative effects. Ideal for straight wall surfaces, borders, and minimalist design styles. IP67 protection, specially in-feed system and end cap design enable a dot-free alignment of numerous fixtures.

Optics & Electronics

Unique integrated circuit design ensures uniform light intensity along the entire length of fixture. LED with 3-step MacAdam and guaranteeing consistency and high quality of light.

Customization

Front, bottom and side cable entry options available for different install options. Endless fixture length configurations allow for the ultimate freedom of design. Cut lengths and terminations are pre-assembled at Vals Lighting factory to ensure IP rating.

Life Cycle

Long lifetime of L70B10>54,000 hours with Five-year limited warranty indoor and outdoor.

VL-SI1212-W (Small Wave series - top bend)



SPECIFICATION LOGIC						
FAMILY	POWER W/m	NOMINAL LENGTH	Light Color	INPUT VOLTAGE	CABLE ENTRY	IP RATING
VL-SI1212-W	9.6W/m	Maximum length - 5m	MONO  TW  RGB  RGBW 	24VDC	FF - Front + Front SS - Side + Side BB - Bottom + Bottom FX - Front + Closed SX - Side + Closed BX - Bottom + Closed	IP67

Order example: VL-SI1212-W-927K-5m-SS

PRODUCT SPECIFICATIONS 				
		MONO		
Electrical	Power	9.6 W/m		
	Input Voltage	24VDC		
Physical	Minimum Length	50mm		
	Width x Height	12mm x 12 mm		
	Body Finish	Premium silicone / white		
	Bend Direction	Vertical (top bending)		
	Bend Radius	50mm		
	Qty of LED	120LEDs/m		
	IC Type	/		
	Cable Entry Options	Front, Side, Bottom		
Optical	Fixture Connections	IP67 injection-moulded input and end cap		
	LED Type	2835 LED		
	Control Protocol	0-10V or PWM or Dali		
	Lumen Output	606Lm/m(3000K)	638Lm/m(4000K)	708Lm/m(6500K)
	Efficacy	66Lm/W(CRI90, 4000K)		
Temperature Range	Lumen Maintenance	L70B10@54,000 hours		
	Storage Temperature	-25°Cmin, 60°Cmax		
	Max Ambient Temperature	50°C		
	Min Ambient Temperature	-25°C		

VL-SI1212-W (Small Wave series - top bend)



PRODUCT SPECIFICATIONS 		
		Tunable white
Electrical	Power	9.6W/m
	Input Voltage	24VDC
Physical	Minimum Length	50mm
	Width x Height	12mm x 12mm
	Body Finish	Premium silicone / white
	Bend Direction	Vertical (top bending)
	Bend Radius	50mm
	Qty of LED	240LEDs/m
	IC Type	/
	Cable Entry Options	Front, Side, Bottom
Optical	Fixture Connections	IP67 injection-moulded input and end cap
	LED Type	2835 LED
	Control Protocol	0-10V or PWM or Dali
	Lumen Output	268Lm/m(2700K) 592Lm/m(4000K) 302Lm/m(6500K)
	Efficacy	61Lm/W(CRI90, 4000K)
Temperature Range	Lumen Maintenance	L70B10@54,000 hours
	Storage Temperature	-25°Cmin, 60°Cmax
	Max Ambient Temperature	50°C
	Min Ambient Temperature	-25°C

PRODUCT SPECIFICATIONS 		
		RGB
Electrical	Power	9.6W/m
	Input Voltage	24VDC
Physical	Minimum Length	50mm
	Width x Height	12mm x 12mm
	Body Finish	Premium silicone / white
	Bend Direction	Vertical (top bending)
	Bend Radius	50mm
	Qty of LED	120LEDs/m
	IC Type	/
	Cable Entry Options	Front, Side, Bottom
Optical	Fixture Connections	IP67 injection-moulded input and end cap
	LED Type	2835 LED
	Control Protocol	PWM or Dali
	Lumen Output	RGB: 328Lm/m
	Efficacy	34Lm/W
Temperature Range	Lumen Maintenance	L70B10@54,000 hours
	Storage Temperature	-25°Cmin, 60°Cmax
	Max Ambient Temperature	50°C
	Min Ambient Temperature	-25°C

VL-SI1212-W (Small Wave series - top bend)



PRODUCT SPECIFICATIONS 		
		RGBW
Electrical	Power	9.6W/m
	Input Voltage	24VDC
Physical	Minimum Length	50mm
	Width x Height	12mm x 12mm
	Body Finish	Premium silicone / white
	Bend Direction	Vertical (top bending)
	Bend Radius	50mm
	Qty of LED	120LEDs/m
	IC Type	/
	Cable Entry Options	Front, Side, Bottom
	Fixture Connections	IP67 injection-moulded input and end cap
Optical	LED Type	2835 LED
	Control Protocol	PWM or Dali
	Lumen Output	RGBW: 336Lm/m
	Efficacy	35Lm/W
	Lumen Maintenance	L70B10@54,000 hours
Temperature Range	Storage Temperature	-25°Cmin, 60°Cmax
	Max Ambient Temperature	50°C
	Min Ambient Temperature	-25°C

VL-SI1212-W (Small Wave series - top bend)



CABLE ENTRY OPTION EXAMPLES

F-FRONT	S-SIDE-LEFT	S-SIDE-RIGHT	B-BOTTOM	SEAMLESS SPLICING
FX 	SLX 	SRX 	BX 	
FF 	SLSL 	SRSR 	BB 	

PROFILES AND MOUNTING OPTIONS

FIXED ALUMINUM PROFILE

	EXAMPLES OF INSTALLATION	PART NUMBER	DETAILS
		1212-FAP-_____ *MM	FAP- Fixed aluminum profile

BENDABLE STAINLESS STEEL PROFILE

	EXAMPLES OF INSTALLATION	PART NUMBER	DETAILS
		1212-BSP-_____ *MM	BSP- Bendable stainless steel profile

MOUNTING CLIPS

	EXAMPLES OF INSTALLATION	PART NUMBER	DETAILS
		1212-MC	MC- Mounting clips

BENDING INSTRUCTION


Bending in wave form - vertical		DO NOT TWIST
DO NOT bend in curve form - horizontal		

VL-SI1212-W (Small Wave series - top bend)

WIRING ELECTRICAL DIAGRAM


MONO

Input by one end



WIRING ELECTRICAL DIAGRAM


Tunable white



VL-SI1212-W (Small Wave series - top bend)

WIRING ELECTRICAL DIAGRAM

RGB



WIRING ELECTRICAL DIAGRAM

RGBW

